

Thank you for your purchase! At MSW® we believe having essential accessories makes a good bike ride great. Pump up your Presta valves with a Schrader pump head. Pretty cool.

▲ WARNING: CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

For additional product and safety information go to: www.mswbike.com/safety.

COMPATIBILITY AND INTENDED USE

Allows the use of a Schrader head pump on a Presta valve.

INSTALLATION

1. Remove the Presta valve cap if there is one.
2. Unscrew the small brass tip at the end of the Presta valve counter-clockwise. It has a built-in stop. Unscrewing it further will remove the valves core. Don't do that.
3. Press the unscrewed tip down until you hear air come out. This is to ensure that the valve is ready to accept air.
4. Place the wide knurled end of the MSW Presta Valve Adapter over the Presta valve and screw it on fully in a clockwise direction.
5. Place the Schrader head of your pump over the threaded end of the adapter and fill the tube to the tire manufacturer's recommended air pressure.
6. Remove the Presta Valve Adapter, close the end of the Presta valve, and replace the valve cap.

▲ WARNING: Use caution when using this product to inflate bicycle tires at a gas station or with a compressor. Gas station air hoses may have unregulated, high pressure that can cause rapid overinflation, resulting in the tire blowing off the rim or bursting.

WARRANTY PROCESS

We will happily back up our products if there is a problem that is our fault! If you think your MSW product is worthy of a warranty inspection, please return the product to the original place of purchase, accompanied by a sales receipt.

For complete warranty information, visit www.mswbike.com/safety/warranty.