

Thank you for your purchase! At MSW® we believe having essential accessories makes a good bike ride great. The MSW Blacktop Trunk Bag installs quickly on your standard rear rack providing quick access with an easy pull-to-open flap. Store your bike lock and keys in dedicated pouches and use the dividers to customize internal organization.

⚠ WARNING: Cycling can be dangerous. Bicycle products should be installed and serviced by a professional mechanic. Never modify your bicycle or accessories. Read and follow all product instructions and warnings including information on the manufacturer’s website. Inspect your bicycle before every ride. Always wear a helmet.

For additional product and safety information, go to: www.mswbike.com/safety.

COMPATIBILITY AND INTENDED USE

The Blacktop Trunk Bag is designed to fit on most standard rear racks. Maximum weight limit: 10kg (22 lb).

⚠ WARNING: Consult manufacturer for maximum weight limit of your rack. To avoid product failure and a possible crash, do not exceed weight limit of the rack or bag.



INTENDED USE: CONDITION 2

This is a set of conditions for the operation of a bicycle that includes Condition 1 as well as unpaved and gravel roads and trails with moderate grades. In this set of conditions, contact with irregular terrain and loss of tire contact with the ground may occur. Drops are intended to be limited to 15cm (6") or less.

BLACKTOP TRUNK BAG CONTENTS



INSTALLATION

1. Center the Trunk Bag on your bicycle rack and slide all four hook-straps downward so the hook ends are all about an equal distance below the Trunk Bag. Loop each hook strap through and around the rack rails (Fig. 1).



Figure 1

2. After looping the hook-strap under the rack rail, pull the strap up and insert the hook into one of the loops. Repeat with all four straps, making sure the straps are tensioned by inserting the hooks into an appropriate loop. (Fig. 2).



Figure 2

INSTALLATION TIP: The first time you install the bag it will take some adjustment to ensure the bag is tight and even. On subsequent installs you will be able to attach to the correct loop without trial and error.

3. To remove, disconnect the hooks from the loops and pull snug to convert to carrying handles. Lift the bag off using the strap handles (Fig. 3) .



Figure 3

USING THE BLACKTOP TRUNK BAG

To open, lift the magnetic flap up and pull flap towards rear of bag (Fig. 4). Store your U-lock in the pocket shown (Fig 5). Secure with hook-and-loop strap. Dividers may be arranged end-to-end (Fig. 6) or in “T” formation (Fig. 7) to customize organization.



Figure 4



Figure 5



Figure 7



Figure 6

▲ WARNING: Entanglement of cargo or straps in your wheel could stop the rotation of the wheel, causing a loss of control or crash that could lead to serious injury. Make sure that the bag, straps, or cargo do not interfere with the function of your bicycle BEFORE attempting to ride. Ensure even cargo distribution, and confirm lights and reflectors are not obstructed by the bag, straps, or cargo.

ONGOING MAINTENANCE

ZIPPER CARE

To ensure reliable performance from zippers, do not try closing the zipper if the bag is overstuffed or when excessive force would be required to close it. Do not force a zipper in an overstuffed pack as this may cause the zipper teeth to come undone from the pack itself and be irreparable. Do not force a slider that has fabric or thread caught in it. Gently pull the slider back and remove the trapped fabric or thread.

FABRIC CARE

Hand wash with warm water and all-purpose detergent. Air dry.

WARRANTY PROCESS

If you and your shop think your MSW product is worthy of a warranty inspection, please return the product to the original place of purchase, accompanied by a sales receipt.

For complete warranty information, visit www.mswbike.com/safety/warranty.